

LY1

GNSS RECEIVER

Powerful, Versatile, Compact, Cost-effective



FULL-CONSTELLATION TRACKING

Featuring 1198 channels for full constellation tracking, LY1 GNSS receiver can deliver reliable centimeter-level accuracy positioning. Benefiting from the strong signal tracking and advanced RTK algorithm, LY1 shows stable & high fixed rate even in harsh environments, such as city canyon, forest and other signal-limited scenarios.



ENHANCED COMMUNICATION

Integrated with enhanced UHF modem¹ and 4G modem inside, LY1 receiver provides fluent and stable data streams between rover and base in long working distance. The enhanced UHF can achieve up to 15km² working range with 2W power, no external radio is required, which is convenient for users to carry on field survey tasks.



VERSATILE FUNCTIONALITY

Aiming to provide users with first-class working experience, LY1 receiver combines all common functionalities in rugged IP67 housing. Equipped with 4G/UHF/WiFi/Blue-tooth for flexible transmission, built-in IMU for 60° tilt measurement, OLED display for status checking, web UI for easy configuration and upgrading, LY1 can always meet your needs.



Lawrence & Mayo

ESTD. 1877

SPECIFICATIONS

SIGNAL TRACKING

Channels	1198
GPS	L1C/A, L2P, L2C, L5, L1C
BDS	B1I, B2I, B3I, B1C, B2a, B2b
GLONASS	L1, L2
Galileo	E1, E5a, E5b, E6, E5 AltBoc
QZSS	L1C, L2, L5, L1C/A
Navic	L5
SBAS	WAAS, EGNOS, SDCM, BDSBAS, GAGAN

ACCURACY

RTK reliability	>99.99%
RTK initialization	< 10s
Hot start	< 15s
Cold start	< 50s
Re-acquisition time	< 1s
Static post-processing	±2.5mm+0.5ppm Horizontally ±5mm+0.5ppm Vertically
RTK	±8mm+1ppm Horizontally ±15mm+1ppm Vertically
RTD	±0.5 m Horizontally ±1.0m Vertically
SBAS	< 1.0 m 3D RMS
Tilt surveying	<2.5cm, within 60° tilt

DATA FORMAT

Data recording formats	RINEX 2.X, 3.X, binary data
Correction data formats	RTCM 2.x, 3.x, CMR
Data output formats	NMEA-0183 messages, binary data
Data output rate	1Hz, 2Hz, 5Hz, 10Hz, 20Hz
Supported protocols	VRS, FKP, MAC, Ntrip

COMMUNICATION

BT	BT4.0
Wi-Fi	IEEE 802.11 a/b/g/n 2.4G 5G, support configuration & data download via web UI
4G	FDD-LTE B1/B3/B5/B7/B8 TDD-LTE B38/B39/B40/B41 TDSCDMA B34/B39 WCDMA B1/B2/B5/B8 GSM B2/B3/B5/B8 CDMA1x/CDMA2000 BC0/BC1
UHF modem ¹	- Frequency range: 410 – 470Mhz - Transmit power: 0.5W/1W/2W selectable - Working range: 5km – 15km ²
Interface	1 7-pin lemo port for RS232 transmission and power supply 1 SIM card slot for 4G 1 TNC connector for UHF antenna

ELECTRICAL

Power	6-28V DC
Battery	6600mAh, 3.6V, more than 12 hours working time
Power consumption	< 2.85 W ³

PHYSICAL

Size	12.3 × 12.3 × 7.0cm
Weight	834 g, with batteries inside
Memory	8 GB
Display	0.93" OLED display
Button	2 buttons for power/enter and function
Indicator	2 LEDs indicating satellite tracking and correction data
Housing	Magnesium-aluminum alloy

ENVIRONMENTAL

Working temperature	-30°C ~ + 65°C
Storage temperature	-40°C ~ +85°C
Waterproof & dustproof	IP67
Shock and Vibration	Designed to survive a 2m drop onto concrete
Humidity	100% no condensation

Note:

- 1.The enhanced UHF modem is not compatible with the normal UHF modem on the market.
- 2.The maximum working range of the enhanced UHF modem is 15km in ideal environments.
3. The power consumption of LY1 varies with the different work modes.

All specifications subject to change without notice.



Lawrence & Mayo (India) Private Ltd.

Registered Office : Lawrence & Mayo House, 274, Dr. D. N. Road, Mumbai-400001. Tel : 022 - 22071828 / 1824 / 6048 Fax : 022 - 2207 0048 Email : instmum@lynxinst.com		Visit : www.lynxinst.com			
AHMEDABAD - 380 006 Tel : 079 - 26400284 / 26077 / 26402754 / 26466160 instahm@lynxinst.com	BANGALORE - 560 002 Tel : 080 - 2221 7900 / 22277901 Fax : 080 - 2224 4492 banstm@lawrenceandmayo.co.in	CHENNAI - 600 002 Tel : 044 - 45939900 Tel : 044 - 28412912 chenmtr@lawrenceandmayo.co.in	COCHIN - 682 011 Tel : 0484 - 4058239 Tel : 0484 - 2368654 inst-coc@lynxinst.com	GOA - 403 001 Tel : 0832 - 2224343 Tel : 0832 - 2431414 goapanj@lawrenceandmayo.co.in	GUWAHATI - 781 005 Tel : 0861-2468994 / 95 instguw@lynxinst.com
NEW DELHI - 110 001 Tel : 011 - 23356262 inst-del@lynxinst.com	PUNE - 411 005 T/F : 020 - 2553 5597 / 3566 puneinst@lynxinst.com	SECUNDERABAD - 500 009 Tel : 040 - 49119972 / 27895015 T/F : 040 - 27898056 insts@lynxinst.com	KOLKATA - 700 014 Tel : 033 - 40511800 Tel : 033 - 40511820/822 instkol@lynxinst.com	ODISHA - 751 001 Tel : 0674 - 2380885 inst-bbsr@lynxinst.com	VISAKHAPATNAM - 530 020 Tel : 0891 - 2505160 invz@lynxinst.com

Dealer: